

INSTALLATION INSTRUCTIONS

- ### Operating Instructions

1. Make sure you keep the water level in the pool midway up the face plate. If the water level falls below the recommended level, water may cavitate in the housing and cause the pool pump to lose its prime.
2. To adjust the inlet flow direction loosen the knurled outer ring of the "eyeball" portion and move the ball to the desired position.

3. To clean the 850V eliminator basket, remove the 8922 top cover; and remove the basket. It is recommended that the pool pump be shut off.
4. To vacuum the pool follow these directions:
 - a. Remove the top cover or fold the 850S-weir flap forward and squeeze pins toward the center and remove. It is not necessary to remove the 850S basket.
 - b. Fill the vacuum hose with water by temporarily inserting the hose into the return fitting while the pool pump is on. Make sure all the air is removed from the hose.
 - c. Take the 8923 Vac adapter, which consists of the plate and elbow, and attach to the hose thru the opening of the wall and place down inside the housing. Try to keep the hose cut submerged during the process so no air will be back into the hose to cause the pump to cavitate and lose its prime.


Winterizing Procedure

Drain pool level approximately 2" to 4" below skimmer opening. Remove the "eyeball" fitting in return and securely plug wall fitting with 1-1/2" plugs from your dealer. Disconnect filter hoses from the skimmer and wall fitting. Be sure that the skimmer is kept free from water accumulation. Your warranty does not cover damages caused by the formation of ice in the skimmer housing.


Parts List

Model 6639 Wide Mouth Thru-Wall Skimmer System includes:

Skimmer Housing
Wide Mouth Extension
8918 Wide Mouth Front Plate
8927 Locking Top Cover
8926 Flap Weir
8928 Basket
8929 Vac Adapter Plate & Elbow
8949 Return Fitting including "Eyeball" and Gaskets
(2) 8905 Hoop Adapters 1-1/4" and 1-1/2"
8917 Wide Mouth Skimmer Gasket Set (2 Pcs.)
Stainless Steel Flaps Screw Set (30) Pcs.- (25) #10 x 1" flat Flips heads
and (4) #10 x 5/8" short pan heads)
8948 Red Teflon Tape



TOP



HOLE TEMPLATE GUIDE